

Appln. No. 09/031,108
CLAIMS SHEET

VERSION SHOWING
CLAIM AMENDMENTS

2. (Twice Amended) A tension member for providing lifting force to a car of an elevator system, the tension member being engageable with a rotatable traction sheave of the elevator system, the tension member comprising:

a plurality of individual load carrying ropes; and

a common layer of polyurethane coating in which the ropes are embedded,
maintaining separation of the individual ropes and resisting longitudinal movement of the ropes relative to one another,

the tension member having a width w, a thickness t measured in the bending direction, and an engagement surface that receives force from the traction sheave as a result of traction between the engagement surface and the traction sheave, which force is transmitted to the ropes of the tension member by the polyurethane coating to thereby move the car, the engagement surface being defined on the polyurethane coating substantially by the width dimension of the tension member, wherein the tension member has an aspect ratio, defined as the ratio of width w relative to thickness t, greater than one, the tension member including a plurality of individual load carrying ropes encased within a common layer of coating, the coating layer separating the individual ropes, wherein the coating layer defines the engagement surface for engaging the sheave.

4. (Twice Amended) A tension member for providing lifting force to a car of an elevator system, the tension member being engageable with a rotateable traction sheave of the elevator system, the tension member comprising:

strands of non-metallic material; and

a polyurethane coating encasing the strands,

the tension member having a width w, a thickness t measured in the bending direction, and an engagement surface that receives force from the traction sheave as a result of traction between the engagement surface and the traction sheave, which force is transmitted to the non-metallic strands of the tension member by the polyurethane coating to thereby move the car, the engagement surface being defined on the polyurethane coating substantially by the width dimension of the tension member,

**Appln. No. 09/031,108
CLAIMS SHEET****VERSION SHOWING
CLAIM AMENDMENTS**

wherein the tension member has an aspect ratio, defined as the ratio of width w relative to thickness t , greater than one, ~~wherein the tension member is formed from strands of non-metallic material.~~

11. (Twice Amended) A tension member for providing lifting force to a car of an elevator system, the tension member being engageable with a ~~non linear~~contoured engagement surface of a ~~-rotateable~~traction sheave of the elevator system, the tension member comprising:

a load-carrying member; and

a polyurethane coating encasing the load-carrying member.

the tension member having a width w , a thickness t measured in the bending direction, and an engagement surface that receives force from the traction sheave as a result of traction between the engagement surface and the traction sheave, which force is transmitted to the load-carrying member of the tension member by the polyurethane coating to thereby move the car. the engagement surface being defined on the polyurethane coating substantially by the width dimension of the tension member, wherein the tension member has an aspect ratio, defined as the ratio of width w relative to thickness t , greater than one, and wherein the engagement surface of the tension member is contoured to complement the ~~non linear~~contoured engagement surface of the sheave.

13. (Twice Amended) A tension member for providing lifting force to a car of an elevator system, the tension member being engageable with a rotatable traction sheave of the elevator system, the tension member comprising:

a load-carrying member; and

a polyurethane coating encasing the load-carrying member.

the tension member having a width w , a thickness t measured in the bending direction, and an engagement surface that receives force from the traction sheave as a result of traction between the engagement surface and the traction sheave, which force is transmitted to the load-carrying member of the tension member by the polyurethane

**Appln. No. 09/031,108
CLAIMS SHEET****VERSION SHOWING
CLAIM AMENDMENTS**

coating to thereby move the car, the engagement surface being defined on the
polyurethane coating substantially by the width dimension of the tension member,
wherein the tension member has an aspect ratio, defined as the ratio of width w relative to
thickness t , greater than one, ~~the tension member including a coating layer formed from~~
~~an elastomer.~~

16. (Twice Amended) A tension member for providing lifting force to a car of an
elevator system, the tension member being engageable with a rotatable traction sheave of
the elevator system, the tension member comprising:

a load-carrying member; and

a polyurethane coating encasing the load-carrying member.

the tension member having a width w , a thickness t measured in the bending direction,
and an engagement surface that receives force from the traction sheave as a result of
traction between the engagement surface and the traction sheave, which force is
transmitted to the load-carrying member of the tension member by the polyurethane
coating to thereby move the car, the engagement surface being defined on the
polyurethane coating substantially by the width dimension of the tension member,
wherein the tension member has an aspect ratio, defined as the ratio of width w relative to
thickness t , greater than one, wherein the engagement surface is shaped to guide the
tension member during engagement with the sheave.

71. (Amended) An elevator system including:

a car;

a traction sheave; and

a tension member engaged with the car, ~~the tension member and~~ engaged
and driven by ~~with~~ the traction sheave, the tension member comprising

a plurality of individual load carrying ropes, and

**Appl. No. 09/031,108
CLAIMS SHEET**

**VERSION SHOWING
CLAIM AMENDMENTS**

a layer of polyurethane coating in which the ropes are embedded,
maintaining separation of the individual ropes and resisting longitudinal
movement of the ropes relative to one another.

the tension member having a width w, a thickness t, and an
engagement surface that receives force from the traction sheave as a result
of traction between the engagement surface and the traction sheave, which
force is transmitted to the ropes of the tension member by the
polyurethane coating to thereby move the car, the engagement surface
being defined on the polyurethane coating substantially by the width
dimension of the tension member.

wherein the tension member has an aspect ratio, defined as the
ratio of width w relative to thickness t, greater than one, ~~the tension~~
~~member including:~~

~~an engagement surface defined by the width dimension of the tension member;~~

~~a plurality of individual lead carrying ropes; and~~

~~a layer of coating, the coating layer separating the individual ropes~~
~~and defining the engagement surface for engaging the sheave.~~

72. (Amended) An elevator system including:

a car;

a traction sheave; and

a tension member engaged with the car, ~~the tension member and engaged with and driven~~
~~by the~~ traction sheave, the tension member comprising

strands of non-metallic material, and

a polyurethane coating encasing the strands.

the tension member having a width w, a thickness t, and an
engagement surface that receives force from the traction sheave as a result
of traction between the engagement surface and the traction sheave, which
force is transmitted to the non-metallic strands of the tension member by

Appln. No. 09/031,108
CLAIMS SHEET

VERSION SHOWING
CLAIM AMENDMENTS

the polyurethane coating to thereby move the car, the engagement surface being defined on the polyurethane coating substantially by the width dimension of the tension member,

wherein the tension member has an aspect ratio, defined as the ratio of width w relative to thickness t , greater than one, ~~the tension member including:~~

~~an engagement surface defined by the width dimension of the tension member;~~

~~and~~

~~strands of non-metallic material.~~

73. (Amended) An elevator system including:

a car;

a traction sheave having a non-linear contoured engagement surface; and

a tension member engaged with the car, ~~the tension member and~~ engaged with and driven by the traction sheave, the tension member comprising

a load-carrying member, and

a polyurethane coating encasing the load-carrying member,

the tension member having a width w , a thickness t , and an engagement surface that receives force from the traction sheave as a result of traction between the engagement surface and the traction sheave, which force is transmitted to the load-carrying member of the tension member by the polyurethane coating to thereby move the car, the engagement surface being defined on the polyurethane coating substantially by the width dimension of the tension member.

wherein the tension member has an aspect ratio, defined as the ratio of width w relative to thickness t , greater than one, ~~the tension member including:~~

~~an engagement surface defined by the width dimension of the tension member, and~~

wherein the engagement surface is contoured to complement the ~~non-linear contoured~~ engagement surface of the sheave.

Appln. No. 09/031,108
CLAIMS SHEET

VERSION SHOWING
CLAIM AMENDMENTS

74. (Amended) An elevator system including:

a car;

a traction sheave having an engagement surface; and

a tension member engaged with the car, ~~the tension member and~~ engaged with and driven by the traction sheave, the tension member comprising

a load-carrying member, and

a polyurethane coating encasing the load-carrying member,

the tension member having a width w, a thickness t, and an engagement surface that receives force from the traction sheave as a result of traction between the engagement surface and the traction sheave, which force is transmitted to the load-carrying member of the tension member by the polyurethane coating to thereby move the car, the engagement surface being defined on the polyurethane coating substantially by the width dimension of the tension member.

wherein the tension member has an aspect ratio, defined as the ratio of width w relative to thickness t, greater than one, ~~the tension member including:~~

~~an engagement surface defined by the width dimension of the tension member, and~~

~~a coating layer formed from an elastomer.~~

75. (Amended) An elevator system including:

a car;

a traction sheave having an engagement surface; and

a tension member engaged with the car, ~~the tension member and~~ engaged with and driven by the traction sheave, the tension member comprising

a load-carrying member, and

a polyurethane coating encasing the load-carrying member,

the tension member having a width w, a thickness t, and an engagement surface that receives force from the traction sheave as a result

**Appln. No. 09/031,108
CLAIMS SHEET****VERSION SHOWING
CLAIM AMENDMENTS**

of traction between the engagement surface and the traction sheave, which force is transmitted to the load-carrying member of the tension member by the polyurethane coating to thereby move the car, the engagement surface being defined on the polyurethane coating substantially by the width dimension of the tension member.

wherein the tension member has an aspect ratio, defined as the ratio of width w relative to thickness t , greater than one, ~~the tension member including:~~

~~an engagement surface defined by the width dimension of the tension member, and~~

wherein the engagement surface is shaped to guide the tension member during engagement with the sheave.